ATAS International, Inc. RAPID-LOK SL COPING - Drive Cleat SPECIFICATION SHEET Sustainable Building Envelope Technology Continuous 1" Support Z -recommended for wall widths 18" and greater Base Membrane 10-9 x 1 1/8" ULP Fastener (32" O.C.) - Stainless Steel 10-9 x 1 1/8" ULP Fastener Coping Cover -32" O.C. (Stainless Steel) **Drive Cleat Splice** (Cut and Bend in Field from 12'-0" Lengths) Continuous 22 GA Front Cleat -Continuous 22 GA Rear Spring Cleat 10-9 x 1 1/8" ULP Fastener --12" O.C. (Stainless Steel) 10-9 x 1 1/8" ULP Fastener -12" O.C. (Stainless Steel) 1 1/4" 3/4" or 3 1/4" 5 1/2" or 1 3/4" 4 3/4" 3/4" Quantity: Total LF (12'-0" pcs) Radius Coping LF (6'-0" pcs) (Radius:____, Convex or Concave) Vaulted Coping LF (6'-0" pcs) (Radius:____, Convex or Concave) **Standard Accessories:** Inside Mitered Corner(s) (Angle:) Outside Mitered Corner(s) (Angle:) End Closure(s) (Left, Right) End Term(s) (Left, Right) **Custom Accessories:** (sketches required) -Inline Transition(s) -Tee(s) -Transition Miter(s) -Zee(s) -Ridge Miter(s) -Special Miter(s) **C DIMENSION H DIMENSION** W DIMENSION -Valley Miter(s) 4-1/2" 5 1/2" - 18" 2-1/2" *All Componets for installing Accessories are included. 5 1/2" - 18" 4" 6" 5 1/2" - 18" 5-1/2" 7-1/2" **MATERIAL: THICKNESS:** 2-1/2" 4-1/2" 18"-32" ☐ Pre-Finished Aluminum ☐ .040 ☐ .050 ☐ .063 6" 18"-32" ☐ Mill Finished Aluminum ☐ .040 ☐ .050 ☐ .063 5-1/2" 7-1/2" 18"-32" ☐ 24 ga ☐ 22 ga ☐ Pre-Finished Steel Job Name: Customer: Representative: Job #: ☐ Stainless Steel ☐ 24 ga ☐ 22 ga Location: Distributor: COLOR: CUSTOMER APPROVAL **ANSI/SPRI ES-1 Tested** Authorized Signature: Projects Requirement's Approved by: Horizontal Design Pressure:___ psf Vertical Design Pressure:____ psf Date: