


**NOTE:**

1. "D" = ROOF PANEL THICKNESS (AVAILABLE THICKNESS = 2.5, 3, 4, 5, OR 6)
2. "W" = WALL PANEL THICKNESS.
3. FILLER INSULATION MATERIAL AND APPLICATION IS SPECIFIED BY THE PROJECT DESIGNER
4. DIMENSIONS SHOW ARE FOR 3" THICK ROOF PANEL. ADJUST DIMENSION PROPORTIONALLY FOR OTHER ROOF PANELS THICKNESS.
5. TRANSITION FLASHING IS INSTALLED WITH A PITCH 1/2:12 GREATER THAN THE ROOF PITCH.

\*\* THE DETAIL SHOWN IS SUBJECT TO CHANGE WITHOUT NOTICE.

|   |   |          |       |
|---|---|----------|-------|
|  | <b>ATAS INTERNATIONAL, INC</b><br>Allentown PA<br>610-395-8445<br>Mesa AZ<br>480-558-7210 |          |       |
| <b>TITLE</b><br>Roof-Sidewall   |   |          |       |
| DWG. NO.  |   | DR       | DATE  |
| MATERIAL  |   | APP      | DATE  |
| REV. NO.  |   | SH. SIZE | SCALE |
| DATE  |   | X:X      |       |
| DESCRIPTION OF REVISION   |   | BY       |       |
| APP   |   | APP      |       |

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |