

PANEL CLIP W/ MIN. (2) 1/4"-14 X _ TEK3
HEX HEAD SDS W/ NON-SKINNING BUTYL
AT POINT OF PENETRATION

NON-SKINNING BUTYL MARRIAGE
BEAD CONNECTING
FINGER JOINT SEALANT TO
NON-SKINNING BUTYL BEAD
BEHIND LINER OF PANEL

12-14 x 1" TEK2 PANCAKE SDS
@ 5'-0" O.C.

HORIZONTAL FRAMING (BY OTHERS)

CONTINUOUS NON-SKINNING BUTYL SEALANT
BETWEEN PANEL AND FLASHING -AND-
BETWEEN FLASHING AND FRAMING

BACKER ROD AND SEALANT
(BY OTHERS)

VERTICAL INSULATED METAL BARRIER PANEL
(VARIOUS PROFILES AVAILABLE)

VARIOUS VERTICAL SINGLE-SKIN WALL
PANELS AND TRIM AVAILABLE THROUGH ATAS

HORIZONTAL SUB-GIRT AVAILABLE THROUGH ATAS,
FASTEN THROUGH INSULATED METAL PANEL
INTO FRAMING, SET FASTENER IN BUTYL
SEALANT AT PENETRATION OF PANEL

1/2" IMP
ABOVE FLASHING

HEAD FLASHING

BACKER ROD AND SEALANT
(BY OTHERS)

WINDOW FRAME (BY OTHERS)

** DETAIL SHOWN IS SUBJECT TO CHANGE WITHOUT NOTICE.



ATAS INTERNATIONAL, INC
Allentown PA
610-395-8445
Mesa AZ
480-558-7210

TITLE
Vertical Barrier Wall- Window Head

REV. NO.	DATE	DESCRIPTION OF REVISION	BY	APP	DWG. NO.	DR	DATE
						APP	DATE
					MATERIAL	SH. SIZE	SCALE X:X