

2 3/8" FIELD-LOK™

SKU: FLS137, FLS180

MATERIAL

.032, .040 aluminum,
24, 22* ga. metallic coated steel,
24 ga. 55% Al-Zn alloy coated steel with acrylic coating

PANEL SPECS

Coverage: 13 3/4", 18"
(Stiffening ribs standard, specify without ribs or striations)
Minimum Length: 4'-0"
Seam Height: 2 3/8"

AVAILABLE

Factory panel pre-notching available.
Contact ATAS for specifics.


TEXTURE

Smooth or Stucco Embossed (available in 24 ga. steel & .032 & .040 aluminum)



MINIMUM SLOPE

1/2:12

www.atas.com/fls



FLS Series standing seam panel features a Triple-Lok design



2" FIELD-LOK™

SKU: FLR154, FLR195, FLR999

MATERIAL

.032, .040 aluminum
24, 22* ga. metallic coated steel
24 ga. 55% Al-Zn alloy coated steel with acrylic coating
16, 20 oz. copper*[^]
.8 mm zinc*[^]
.0197 classic & tin matte stainless steel*[^]
[^]Inquire for available panel widths

PANEL SPECS

Coverage: 15 1/4", 19 1/2"
Custom widths available (Plank ribs standard, specify without ribs or striations)
Minimum Length: 4'-0"
Seam Height: 2"

AVAILABLE

Tapered
Factory panel pre-notching available.
Contact ATAS for specifics.

TEXTURE

Smooth or Stucco Embossed (available in 24 ga. steel & .032 aluminum)

MINIMUM SLOPE

1/2:12

www.atas.com/flr